

evoclear

HIGH PERFORMANCE FILTERS

OPAL SERIES

CARTRIDGE FILTERS



Installation and Operation Manual

OPAL 135 | OPAL 180

WARNING

This equipment must be installed and serviced by a qualified technician. Improper installation can create electrical hazards which could result in property damage, serious injury or death. Improper installation will void the warranty.



Notice to Installer

This manual contains important information about the installation, operation and safe use of this product. Once the product has been installed **this manual must be given to the owner/operator of this equipment.**



evoclear

HIGH PERFORMANCE FILTERS

OPAL SERIES

CARTRIDGE FILTERS



Installation and Operation Manual

OPAL 135 | OPAL 180

1.0	INTRODUCTION	3
2.0	INSTALLATION	3
3.0	START UP PROCEDURE	4
4.0	MAINTENANCE	4
5.0	CLEANING	5
6.0	TROUBLESHOOTING.....	6

1.0 INTRODUCTION

- 1.1.1 Congratulations on your recent purchase of an Evolution Evoclear Cartridge Filter. Please take a moment to read through the entire manual before using the filter. The filter must be installed and operated as specified.
- 1.1.2 Evoclear Cartridge Filters do not require a media such as sand or D.E powder to operate, instead the filter contains a cartridge element which is easily removed to clean or replace.
- 1.1.3 All Evoclear Cartridge Filters are ideal for use in swimming pools and spas. Evoclear Cartridge Filters are also ideal for use when backwashing is impractical.

2.0 INSTALLATION

- 2.1.1 Remove the cartridge filter from the carton and install the pressure gauge into the threaded port on the filter lid provided. Using Teflon, wrap once around the brass pressure gauge thread in a clockwise direction and screw into the threaded lid port.
- 2.1.2 **⚠CAUTION:** Hand tighten the pressure gauge into the lid only for sealing.
- 2.1.3 Place the Cartridge Filter into the required position. Ensure that it is on a flat level surface and is aligned with the pump.
- 2.1.4 The Cartridge Filter has marked inlet and outlet ports. Ensure that the pipe extending from the pump outlet is connected to the Cartridge Filter marked inlet.
- 2.1.5 Screw the supplied half barrel unions and tails onto the inlet and outlet before gluing the UPVC piping onto the filter.
- 2.1.6 **⚠CAUTION:** Use only the recommended glue for the connection pipes and fittings.
- 2.1.7 Cut and fit the pipe and fittings onto the pump and the Cartridge Filter. REFER to Pump Installation Manual for correct pump plumbing procedures.
- 2.1.8 It is best practice to fit all the cut pipe and fittings onto the filtration system before gluing; this will ensure that the system has been aligned correctly.
- 2.1.9 Glue the pipe and fittings onto the pump, filter and pool return lines and allow the glue to set for 24 hours before commissioning the system.
- 2.1.10 It is advisable to bolt the filter down to the floor where the filter is located. This will prevent the filtration plumbing from working loose with the expansion and operation of the filter during regular cycles. It will also help to prevent unnecessary stress on the plumbing while unscrewing the filter lid locking ring.

3.0 START UP PROCEDURE

- 3.1.1 To start up the filtration system either from new or after cleaning is exactly the same.
1. Ensure that all valves installed before or after the filter are open.
 2. Ensure that the filter is plumbed correctly. Pipe from pump outlet must be attached to the filter inlet port.
 3. Loosen the air bleed screw on top of the filter lid.
 4. Prime the swimming pool pump. (Refer to the pump installation and operation manual).
 5. Turn on the swimming pool pump and allow the pump to run until all the air has been expelled from the filter vessel. Water will run from the air bleed screw.
 6. Tighten the air bleed screw.
 7. The filter is primed and ready for operation.
- 3.1.2 In some cases this may be required to be done a few times before the unit will remain primed and be fully operational.
- 3.1.3 **⚠CAUTION:** Do not stand over the lid whilst adjusting the air bleed to purge the system of air. Injury may occur if air bleed screw comes loose.

4.0 MAINTENANCE

- 4.1.1 To ensure that you get maximum life from your Cartridge Filter you will need to maintain the filter regularly.
- 4.1.2 When the filter is first started and has been purged of air, note the pressure on the pressure gauge. This is what is known as the filter operation pressure and it is important that you be aware of this figure.
- 4.1.3 All filtration systems will operate at different pressures depending on the pool hydraulics.
- 4.1.4 You will need to clean the filter cartridge (element) once the pressure gauge has reached 50 kPa above the operating pressure.
- 4.1.5 The Evoclear Cartridge Filters have a maximum operating pressure of 350 kPa.

5.0 CLEANING

5.1.1 To clean the Evoclear Cartridge Filter Element, carry out the following procedure.

1. Unscrew the filter lid locking ring and remove the lid off the filter tank. In some cases where pressure has built up you will need to release air from the tank using the air bleed screw before removing the lid.

2. Remove the cartridge element from the filter tank.

3. Using a garden type hose clean the surface of the pleated elements. Make sure to clean between the pleats.

4. Place the cartridge back into the filter tank ensuring that it is seated correctly.


5. Ensure the lid o-ring is correctly seated on the lid groove, and lubricate with a suitable silicone lubricant if required.

6. Push the lid onto the tank and screw the locking ring down.

7. Refer to the start up procedure to re-commence operation.

5.1.2 It is suggested that you should periodically remove the cartridge filter element and soak it overnight in a suitable cartridge cleaning compound. This will remove any debris not removed by hosing down of the element.

5.1.3 The cleaning time depends upon the swimming pool condition and use. Intervals between cleaning the element should not exceed a period of 12 months in any instance.



FLOW DIAGRAM

6.0 TROUBLESHOOTING

SYMPTOMS	POSSIBLE PROBLEMS / SOLUTIONS
Water is not clear	Insufficient disinfectant level.
	Incorrect pool chemistry.
	Heavy bathing and/or dirt loads.
	Incorrect flow.
	Insufficient running times = Increase pump run time.
	Filter is dirty. Clean per instructions.
	Hole in filter element.
Low water flow	Check strainer baskets for debris.
	Check for air leaks on suction side.
	Check for restrictions or blockage in either suction or return lines.
	Filter needs to be cleaned or replaced.
	Pool water level too low.
	Pump not primed.
	Pump impeller vanes blocked.
	Strainer baskets not being used and/ or not being cleaned regularly.
	Pump operating under speed (low voltage).
Short filter cycles	Presence of algae, check disinfectant content.
	Check pH and total alkalinity.
	Pump output exceeds design flow rate of filter, check pump performance.
	Ineffective cleaning, check conditions, replace filter cartridge.
High pressure on start-up	Small eyeball fitting in Pool/ Spa.
	Partially closed valve on return line.
	Too large of pump, check selection.
Dirt returns to pool	Hole in filter cartridge, replace filter cartridge.
	Worn o-ring seal inside filter, replace o-ring.



Evolution Water & Lighting Solutions

Phone: +61 7 5565 0000
Fax: +61 7 5565 0010
Email: enquiries@evolutionwls.com.au
Web: www.evolutionwls.com.au
Address: 27/30 Mudgeeraba Rd,
Worongary QLD 4213 Australia

Evoclear Opal Manual - V1